CLAIMS:

- A method of estimating computing system resource
 usage for each transaction type, comprising the steps of,
 - obtaining utilisation data of a system resource for each resource type and transaction count data for each transaction type as input data, and
- opplying a linear least squares algorithm to the input data to provide an estimate of resource usage for an individual transaction type within the computing environment,
- wherein the application of the linear least squares algorithm comprises the further steps of,
 - providing a matrix, the size of the matrix being defined by the number of transaction types and the number of resource types,
- storing the sum of the cross-products of each resource type and each transaction type in the matrix,
 - storing the sum of the cross-products of each transaction type with each other transaction type in the matrix, and
- 25 at selected time intervals, applying a further mathematical algorithm to derive an estimate of the resource usage per transaction type.
- A method in accordance with claim 1, comprising the further step of dividing the computation into separate sub-parts.
 - 3. A method in accordance with claim 1 or claim 2, wherein the utilisation data includes a resource utilisation value for each resource type for each given time interval, and the transaction count data includes the total number of
- transactions executed for each transaction type in each given time interval.
 - 4. A method in accordance with claim 2 or claim 3, wherein

WO 2004/059501 PCT/US2002/041622

- 22 -

the number of calculations required to produce an estimate of resource usage by transaction type are reduced by computing a select number of cross-products from the total number of possible cross-products in the matrix.

5. A method in accordance with claim 4, wherein the mathematical algorithm is the Cholesky method.

5

15

30

- 6. A system for estimating computing system resource usage for each transaction type, comprising,
- of a system resource for each resource type and transaction count data for each transaction type as input data, and
 - means for applying a linear least squares algorithm to the input data to provide an estimate of resource usage for an individual transaction type within the computing environment,

wherein the means for the application of the linear least squares algorithm further comprises,

- means for providing a matrix, the size of the matrix
 being defined by the number of transaction types and
 the number of resource types,
 - means for storing the sum of the cross-products of each resource type and each transaction type in the matrix,
- 25 means for storing the sum of the cross-products of each transaction type with each other transaction type in the matrix, and

means for, at selected time intervals, applying a further mathematical algorithm to derive an estimate of the resource usage per transaction type.

- 7. A system in accordance with claim 6, further comprising means for dividing the computation into separate subparts.
- 8. A system in accordance with claim 6 or claim 7, wherein the utilisation data includes a resource utilisation value for each resource type for each given time interval, and the transaction count data includes the total number of

WO 2004/059501 PCT/US2002/041622

- 23 -

transactions executed for each transaction type in each given time interval.

- 9. A system in accordance with claim 7 or claim 8, wherein the number of calculations required to produce an estimate of resource usage by transaction type are reduced by computing a select number of cross-products from the total number of possible cross-products in the matrix.
- 10. A system in accordance with claim 9, wherein the mathematical algorithm is the Cholesky method.
- 10 11. A computing program arranged, when loaded on a computing system, to control the computing system to implement the method of any one of claims 1 to 5.

5

12. A computer readable medium providing a computer program in accordance with claim 11.